

PRODUCT SPECS



150mm Width



Product Code:	WS-Poly-Black
Diameter	1650mm
Height	100mm
Width:	150mm
Weight:	4.5kg
Colours:	Yellow, Grey, Black, Blue, Green, Orange
Fixing:	3 Fixings, Cover Plugs included. 16mm Sleeve Anchor Bolt for Concrete, or 14mm Galvanized Spikes for Asphalt



POLY WHEEL STOP

- Manufactured from ultra-tough Linear Low-Density Polyethylene (LLDPE)
- Australian Standards Approved
- Light weight easy to install by one person
- Most durable wheel stops on the market
- Fixing Bolts Included (Concrete or Asphalt)
- Installation Service is available

Enforcer Poly Wheel Stop comply to AS/NZS 2890.1:2004, Environmentally friendly Poly (LLDPE)

Manufactured from ultra-tough Linear Low-Density Polyethylene (LLDPE). One piece moulded, lightweight very easy to install by one Person, designed to be Strong and durable, these wheel stops will not warp, crack, chip or rot. Solid colour.

Available in Safety Yellow for high visibility and pedestrian safety, Blue for disabled parking spaces, Black and Concrete Grey. Finished with nice curved edges to avoid trip hazard. Suited to use in Concrete or Asphalt for Schools, Hospitals, Airports, Factories, Warehouses and all Indoor and outdoor Car parks.



Strong & Durable



Australian Standards Approved



Easy Installation



Call us 1300 85 40 10